

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-16. Canceled.

17. (Currently Amended) A method of processing user speech data at a processing entity for transmission to a participant or participants in a push to talk session over a communications network, the method comprising: following initiation of a push to talk session, but prior to receipt by the entity of a session acceptance from the or each participant;
~~analysing~~ analyzing the speech data to identify an initial period of silence; and
removing ~~an~~ the initial period of silence from the speech data prior to sending the speech data to a receiving terminal of the or each other participant.

18. (Previously Presented) A method according to claim 17, wherein said speech data is an initial speech burst provided by the initiating party of the push to talk session.

19. (Previously Presented) A method according to claim 17, wherein said communication network is a cellular telephone network and the push to talk service is a Push to talk Over Cellular service.

20. (Currently Amended) A method according to claim 17, wherein said step of ~~analysing~~analyzing the speech data to identify an initial period of silence is carried out at a terminal of the initiating party or a node within the communication network.

21. (Previously Presented) A method according to claim 17, wherein the step of removing an initial period of silence from the transmitted speech data is carried out at a terminal of the initiating party or a node within the communication network.

22. (Previously Presented) A method according to claim 21, wherein the network node is a Media Resource Function node.

23. (Previously Presented) A method according to claim 21, wherein the network node is located within an IP Multimedia Subsystem (IMS).

24. (Previously Presented) A method according to claim 17, further comprising monitoring the audio level to determine when speech has started.

25. (Previously Presented) A method according to claim 17, further comprising predefining an initial period expected to contain silence, and clipping the start of the speech data remove the predefined period.

26. (Currently Amended) A method according to claim 25, wherein the predefined period is fixed or is adapted in dependence upon subscriber ~~behaviour~~behavior.

27. (Currently Amended) A server node for use in a communication network offering a push to talk service to subscribers, the node comprising:

a receiver ~~for receiving~~ configured to receive a speech burst from a participant in a push to talk session; and

a processor configured for, following initiation of a push to talk session but prior to receipt by the network of a ~~session~~ session acceptance from a receiving participant, to:

~~detecting~~ detect an initial period of silence in the speech data burst; and

~~removing~~ remove the detected period of silence from the speech data prior

to transmission to the or each other participant in the session.

28. (Previously Presented) A server node according to claim 27 and being arranged to be located within an IP Multimedia Subsystem of a cellular telephone communications network, the node having an interface to one or more Session Initiation Protocol (SIP) servers including a Serving Call Session Control Function (S-CSCF) server.

29. (Currently Amended) A mobile terminal for use in a communication network offering a push to talk service to subscribers, the terminal comprising:

a receiver ~~for receiving~~ configured to receive speech data from a terminal user;
and

a processor configured for, following initiation of a push to talk session, but prior to receipt by the mobile terminal of a session acceptance from a receiving terminal, to:

~~removing~~remove a period of silence from the speech data prior to transmission to the or each other terminal participating in the session.

30. (Previously Presented) A terminal according to claim 29, the terminal being a wireless terminal and the communication network being a cellular telephone network offering a Push to talk Over Cellular service.

31. (Previously Presented) A terminal according to claim 29, wherein the receiver comprises means for converting speech into an analogue or digital electrical signal.

32. (Previously Presented) A terminal according to claim 29, wherein the receiver comprises means for receiving speech data over an interface link to said communication network, the speech data having been generated at a peer mobile terminal.

33. (New) A server node according to claim 27, wherein the processor is configured to analyze the speech data to identify the initial period of silence following initiation of a push to talk session, but prior to receipt by the entity of a session acceptance from the or each participant and prior to removing the detected period of silence.

34. (New) A terminal according to claim 29, wherein the processor is configured to analyze the speech data to identify the initial period of silence following initiation of a push to talk session, but prior to receipt by the mobile terminal of the session acceptance from the receiving terminal and prior to removing the period of silence from the speech data.